

## Maticové závitníky

cylindrický trubkový závit



### HSS-G

## Rp (BSPP)

| Jmenovitý rozměr<br>D | L 1 | L 2 | D 2 | ☑ | obj.č. |
|-----------------------|-----|-----|-----|---|--------|
|-----------------------|-----|-----|-----|---|--------|

#### Forma C

|               |     |    |      |      |       |
|---------------|-----|----|------|------|-------|
| PS 1/16 x 28  | 55  | 19 | 6.5  | 5.0  | 95402 |
| PS 1/8 x 28   | 55  | 19 | 8.0  | 6.0  | 95406 |
| PS 1/4 x 19   | 62  | 28 | 11.0 | 9.0  | 95414 |
| PS 3/8 x 19   | 65  | 28 | 14.0 | 11.0 | 95418 |
| PS 1/2 x 14   | 80  | 35 | 18.0 | 14.0 | 95422 |
| PS 3/4 x 14   | 85  | 35 | 23.0 | 17.0 | 95430 |
| PS 1" x 11    | 95  | 45 | 26.0 | 21.0 | 95438 |
| PS 1.1/4 x 11 | 105 | 45 | 32.0 | 26.0 | 95446 |
| PS 1.1/2 x 11 | 110 | 45 | 38.0 | 29.0 | 95454 |
| PS 2" x 11    | 120 | 50 | 46.0 | 35.0 | 95470 |

#### Forma C, 35° pravotočivá spirála

|               |     |    |      |      |       |
|---------------|-----|----|------|------|-------|
| PS 1/16 x 28  | 55  | 19 | 6.5  | 5.0  | 95702 |
| PS 1/8 x 28   | 55  | 19 | 8.0  | 6.0  | 95706 |
| PS 1/4 x 19   | 62  | 28 | 11.0 | 9.0  | 95714 |
| PS 3/8 x 19   | 65  | 28 | 14.0 | 11.0 | 95718 |
| PS 1/2 x 14   | 80  | 35 | 18.0 | 14.0 | 95722 |
| PS 3/4 x 14   | 85  | 35 | 23.0 | 17.0 | 95730 |
| PS 1" x 11    | 95  | 45 | 26.0 | 21.0 | 95738 |
| PS 1.1/4 x 11 | 105 | 45 | 32.0 | 26.0 | 95746 |
| PS 1.1/2 x 11 | 110 | 45 | 38.0 | 29.0 | 95754 |
| PS 2" x 11    | 120 | 50 | 46.0 | 35.0 | 95770 |

#### Použití:

##### pro všeobecné nasazení

- dobře obrobitelné materiály do 900 N/mm<sup>2</sup>
- nelegované a nízkolegované oceli
- pro ruční a strojní nasazení

**Form C:** pro průchozí díry

**35° RSP:** pro slepé díry

