

Sadové závitníky

Whitworth-závit BS 84



≈ DIN 352 HSS-G

BSW

Jmenovitý rozměr D	L 1	L 2	D 2	☑	obj.č.
1/16 x 60	36	10	2.5	2.1	22302
3/32 x 48	36	10	2.8	2.1	22304
1/8 x 40	40	12	3.5	2.7	22306
5/32 x 32	45	14	4.5	3.4	22308
3/16 x 24	50	18	6.0	4.9	22310
7/32 x 24	50	18	6.0	4.9	22312
1/4 x 20	50	19	6.0	4.9	22314
5/16 x 18	56	22	6.0	4.9	22316
3/8 x 16	70	24	7.0	5.5	22318
7/16 x 14	70	24	8.0	6.2	22320
1/2 x 12	75	29	9.0	7.0	22322
9/16 x 12	80	30	11.0	9.0	22324
5/8 x 11	80	32	12.0	9.0	22326
3/4 x 10	95	40	14.0	11.0	22330
7/8 x 9	100	40	18.0	14.5	22334
1" x 8	110	50	18.0	14.5	22338
1.1/8 x 7	132	56	22.0	18.0	22342
1.1/4 x 7	132	56	22.0	18.0	22346
1.3/8 x 6	150	63	28.0	22.0	22350
1.1/2 x 6	150	63	32.0	24.0	22354
1.5/8 x 5	160	70	32.0	24.0	22358
1.3/4 x 5	160	70	36.0	29.0	22362
1.7/8 x 4.1/2	190	80	36.0	29.0	22366
2" x 4.1/2	190	80	40.0	32.0	22370
2.1/4 x 4	220	80	45.0	35.0	22372
2.1/2 x 4	220	80	50.0	39.0	22374
2.3/4 x 3.1/2	240	80	50.0	39.0	22376
3" x 3.1/2	260	80	50.0	39.0	22378

Použití:

pro všeobecné nasazení

- dobře obrobitelné materiály do 900 N/mm²
- nelegované a nízkolegované oceli
- pro průchozí a slepé díry
- pro ruční použití

Příklad objednávky:

BSW 1/8 = 22306
BSW 1/8, č. 1 = 22306-1
BSW 1/8, č. 2 = 22306-2
BSW 1/8, č. 3 = 22306-3

